

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number
WO 2004/001496 A1

(51) International Patent Classification⁷: G02F 1/155

(21) International Application Number:
PCT/IB2003/002628

(22) International Filing Date: 12 June 2003 (12.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02254373.0 24 June 2002 (24.06.2002) EP

(71) Applicant (for all designated States except US): KONIN-
KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): JOHNSON, Mark,
T. [GB/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eind-
hoven (NL). YOUNG, Nigel, D. [GB/GB]; c/o Prof. Hol-
stlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: DEGUELLE, Wilhelmus, H., G.; internationaal
Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eind-
hoven (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,
SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: ELECTROCHROMIC DISPLAY PANEL WITH ELECTRODES FOR ADJUSTING CROSSTALK



(57) Abstract: The display panel (1) has multiple picture elements (2), each picture element (2) having respective neighboring picture elements (2'). The picture elements (2) have a first electrode (3) and a second electrode (4) for the application of a potential difference between the first and the second electrode (3,4), and electrochromic material (5), which is present between the first and the second electrode (3,4). Electrical charge contained by the electrochromic material (5), induced by the potential difference, determines the color of the picture element (2). Color changes are provided by varying the electrical charge. Crosstalk, being coloration of neighboring picture elements (2') when a picture element (2) is addressed, is adjustable by third electrodes (6) which adjust electrical currents between the picture element (2) addressed and their respective neighboring picture elements (2').